Stock Model	Average Weight	<u>LOP</u>	Overall Length	Forend Width	Right or Left Handed	Bi Pod and Pic Rail Compatible*	<u>Tri-Pod</u> <u>Compatible *</u>	QD Cup Compatible *	Slings Studs Included	Drop of the Comb from center bore	Drop of the buttpad from center bore
AG Privateer	24 oz.	13.5	29.5"	1.51"	Yes	Yes	Yes	Yes	2	.625 inches	.325 inches
AG Sportsman	26 oz.	13.5	30.8"	1.75"	Right Only	Yes	Yes	Yes	2	.625 inches	.375 inches
AG Carbon All Terrain (CAT)	26 oz.	13.5"	30.8"	1.75"	Yes	Yes	Yes	Yes	2	.625 inches	.375 inches
AG Visigoth	28 oz.	13.5"	30.9"	1.8"	Yes	Yes	Yes	Yes	3	.25 inches	.2 inches
AG Chalk Branch	31 oz.	13.5"	31"	2"	Yes	Yes	Yes	Yes (only in buttstock)	3	.2 inches	.2 inches
AG Alpine Hunter	31 oz.	13.5"	30.9"	1.8"	Yes	Yes	Yes	Yes	3	.2 inches	.2 inches
AG Gladius	34 oz.	13.5"	30.9"	2.375"	Yes	Yes	Yes	Yes	3	.2 inches	.2 inches
AG Adjustable Gladius	42 oz.	13.5"	30.9"	2.375"	Yes	Yes	Yes	Yes	3	.2 inches with cheek riser at lowest position	.2 inches
AG Adjustable Chalk Branch	40 oz.	13.5"	31	2"	Yes	Yes	Yes	Yes (only in buttstock)	3	.2 inches with cheek riser at lowest position	.2 inches
AG Adjustable Hunter	40 oz.	13.5"	30.9"	1.8"	Yes	Yes	Yes	Yes	3	.2 inches with cheek riser at lowest position	.2 inches

NOTE: Stocks that are finsihed with the Carbon Fiber exposed option can be 1 to 2 ounces lighter than the weights listed above.

* Customize your stock:

- 1) All AG stocks come with a 6" to 9" long, 1/4" thick aluminum insert inside the forend of the stock. The end user or AG can drill and tap holes into this insert for additional swivel study or rails.
- 2) AG can drill and tap two 1/4 20 threaded holes forward of the recoil lug to accommodate a tri-pod.
- 3) Stocks that have two slings swivels installed, the swivels are approximately 2.5" apart.
- 4) LOP Adjustments can be made. Some restrictions apply. Contact us for more details.