

<u>Stock Model</u>	<u>Average Weight</u>	<u>LOP</u>	<u>Overall Length</u>	<u>Forend Width</u>	<u>Right or Left Handed</u>	<u>Bi Pod and Pic Rail Compatible*</u>	<u>Tri-Pod Compatible *</u>	<u>QD Cup Compatible *</u>	<u>Slings Studs Included</u>	<u>Drop of the Comb from center bore</u>	<u>Drop of the buttpad from center bore</u>
AG Privateer	25 oz.	13.5	29.5"	1.51"	Yes	Yes	Yes	Yes	2	.625 inches	.325 inches
AG Sportsman	27 oz.	13.5	30.8"	1.75"	Right Only	Yes	Yes	Yes	2	.625 inches	.375 inches
AG Carbon All Terrain (CAT)	27 oz.	13.5"	30.8"	1.75"	Yes	Yes	Yes	Yes	2	.625 inches	.375 inches
AG Visigoth	28 oz.	13.5"	30.9"	1.8"	Yes	Yes	Yes	Yes	3	.25 inches	.2 inches
AG Chalk Branch	31 oz.	13.5"	31"	2"	Yes	Yes	No	Yes (only in buttstock)	3	.2 inches	.2 inches
AG Alpine Hunter	31 oz.	13.5"	30.9"	1.8"	Yes	Yes	Yes	Yes	3	.2 inches	.2 inches
AG Carbon K2	34 oz.	13.5"	32.25	1.875	Yes	Yes	Yes	Yes	3	.2 inches	.2 inches
AG Armor (formerly the Gladius)	34 oz.	13.5"	30.9"	2.375"	Yes	Yes	Yes	Yes	3	.2 inches	.2 inches
AG Ferrata	34 oz.	13.5"	32.3"	1.75"	Yes	Yes	Yes	Yes	3	.2 inches	.2 inches
AG Adjustable Armor (formerly the Adj Gladius)	42 oz.	13.5"	30.9"	2.375"	Yes	Yes	Yes	Yes	3	.2 inches with cheek riser at lowest position	.2 inches
AG Adjustable Chalk Branch	40 oz.	13.5"	31	2"	Yes	Yes	No	Yes (only in buttstock)	3	.2 inches with cheek riser at lowest position	.2 inches
AG Adjustable Hunter	40 oz.	13.5"	30.9"	1.8"	Yes	Yes	Yes	Yes	3	.2 inches with cheek riser at lowest position	.2 inches
AG Carbon K2 Adjustable	42 oz.	13.5"	32.25"	1.875"	Yes	Yes	Yes	Yes	3	.2 inches with cheek riser at lowest position	.2 inches

NOTE: Stocks that are finished with the Carbon Fiber exposed option can be 1 to 2 ounces lighter than the weights listed above.

*** Customize your stock:**

- 1) All AG stocks come with a 6" to 9" long, 1/4" thick aluminum insert inside the forend of the stock. The end user or AG can drill and tap holes into this insert for additional swivel studs or rails.
- 2) AG can drill and tap two 1/4 20 threaded holes forward of the recoil lug to accommodate a tri-pod.
- 3) Stocks that have two slings swivels installed, the swivels are approximately 2.5" apart.
- 4) LOP Adjustments can be made. Some restrictions apply. Contact us for more details.